



# Sporicidin® Mold Resistant Coatings

Easy to use coating prevents the growth of mold on the coating film when applied to porous and/or non-porous

Sporicidin® Mold Resistant Coating is an easy-to-use, water-based permanent coating that incorporates a unique zero VOC, EPA registered antimicrobial that prevents the growth of mold on the coating film. Developed for high moisture areas, this product forms a dehydration finish that does not allow moisture penetration, thus preventing the growth of mold on the film. The quality of the product, along with the anti-abrasion\* and anti-scratch qualities, exceed the performance requirements of the following microbiological resistant tests: ASTM D3273, D3274.

Sporicidin Mold Resistant Coatings can be used on any new or existing building material before, during, or after installation. It quickly penetrates and adheres to porous and non-porous surfaces, providing a stain-blocking coating that will not blister, crack, or chip and restores the integrity of damaged materials.



## PERFORMANCE CHARACTERISTICS:

- Mold resistance on the film
- Special UV detectable pigment for warranty verification
- Non-leaching and non-toxic
- Excellent longevity
- Bonds to organic and inorganic surfaces
- Superior moisture prevention
- Breathable and paintable
- Designed to provide a uniform primer or can be left as the top coat
- Features phenomenal hiding and enamel holdout
- Nanotechnology provides excellent durability and adhesion
- Provides protection from water penetration
- Seals water extractives and tannins in redwood and cedar
- Dry to touch time: 30 min. to 60 min. depending on product used, temperature and humidity
- Shelf life: three years
- Air Quality and Management District (AQMD) and VOC compliant

## IT CAN BE APPLIED TO:

- Lumber
- Particle board
- Walls
- Ceilings
- Subfloors
- Ductwork
- Wood
- Drywall
- Mineral substrates\*\*

\*\* It aids in deodorizing and eliminating odors while providing a paint-like film on interior and exterior surfaces that can be sanded and recoated without the obnoxious fumes like competitive products.

\* When applied correctly, the film bonds to the surface and lasts for a long period of time however, abrasion can eventually harm the film when the surface is not cared for properly.

Note: Always test on inconspicuous areas prior to full application.



Contec Cleaning and Restoration Products

P.O. Box 530 • Spartanburg, SC 29304 USA  
Tel: +1-864-503-8333  
Toll Free (US, Canada, PR): 1-800-289-5762  
www.sporicidin.com • sporicidin@contecinc.com



# Sporicidin® Mold Resistant Coatings

Easy to use coating prevents the growth of mold on porous and non porous surfaces.

## SELECT THE RIGHT PRODUCT

Part Number	Coverage	Color
MRC-80	Up to 1,000 sq.ft./gallon	Clear
MRC-100	Up to 400 sq.ft./gallon	White

## FURTHER QUESTIONS?

Technical Information is also available on these and other Sporicidin® Brand Products.

Ask your sales rep for more information.

Part No.	Description	Packaging
MRC-80-1	Sporicidin Mold Resistant Coating, 1 Gallon (3.7L) container, Clear, UV Indicator	4 containers/case
MRC-80-5	Sporicidin Mold Resistant Coating, 5 Gallon (18.9L) container, Clear, UV Indicator	1 container/case
MRC-100-1	Sporicidin Mold Resistant Coating, 1 Gallon (3.78L) container, White	4 containers/case
MRC-100-5	Sporicidin Mold Resistant Coating, 5 Gallon (18.9L) container, White	1 container/case



Contec Cleaning and Restoration Products

P.O. Box 530 • Spartanburg, SC 29304 USA  
 Tel: +1-864-503-8333  
 Toll Free (US, Canada, PR): 1-800-289-5762  
 www.sporicidin.com • sporicidin@contecinc.com